



XHTML+RDFa 1.1

Support for RDFa via XHTML Modularization

W3C Working Draft 22 April 2010

This version:

<http://www.w3.org/TR/2010/WD-xhtml-rdfa-20100422/>

Latest published version:

<http://www.w3.org/TR/xhtml-rdfa/>

Latest recommendation:

<http://www.w3.org/TR/rdfa-syntax/>

Editor:

Shane McCarron, Applied Testing and Technology, Inc.

This document is also available in these non-normative formats: Postscript version and PDF version.

Copyright © 2007-2010 W3C® (MIT, ERCIM, Keio), All Rights Reserved. W3C liability, trademark and document use rules apply.

Abstract

RDFa Core 1.1 [RDFA-CORE [p.59]] defines attributes and syntax for embedding semantic markup in Host Languages. This document defines one such Host Language. This language is a superset of XHTML 1.1 [XHTML11-2e [p.59]], integrating the attributes as defined in RDFa Core 1.1. This document is intended for authors who want to create XHTML-Family documents that embed rich semantic markup.

Status of This Document

This section describes the status of this document at the time of its publication. Other documents may supersede this document. A list of current W3C publications and the latest revision of this technical report can be found in the W3C technical reports index at <http://www.w3.org/TR/>.

This is a revision of Sections 8 and 9 and Appendix A of RDFa Syntax 1.0 [RDFA-SYNTAX [p.59]]. Once development is complete, if accepted by the W3C membership, this document will supersede those sections of the previous Recommendation. There are a number of substantive differences between this version and its predecessor, including:

C. Deployment Advice	52
D. Change History	53
E. Acknowledgments	55
F. References	57
F.1 Normative references	59
F.2 Informative references	59

1. Introduction

XHTML+RDFa 1.1 is an XHTML family markup language. It extends the XHTML 1.1 markup language with the attributes defined in RDFa Core 1.1. The document also defines an XHTML Modularization-compatible [XHTML-MODULARIZATION11-2e [p.59]] module for the RDFa Core attributes in both XML DTD and XML Schema formats.

2. Conformance

As well as sections marked as non-normative, all authoring guidelines, diagrams, examples, and notes in this specification are non-normative. Everything else in this specification is normative.

The key words *must*, *must not*, *required*, *should*, *should not*, *recommended*, *may*, and *optional* in this specification are to be interpreted as described in [RFC2119 [p.59]].

2.1 Document Conformance

A strictly conforming XHTML+RDFa document is a document that requires only the facilities described as mandatory in this specification. Such a document satisfies the following criteria:

1. The document *must* conform to the constraints expressed in the schemas in Appendix A - XHTML+RDFa XML Schema [p.17] and Appendix B - XHTML+RDFa Document Type Definition [p.39] .
2. The local part of the root element of the document *must* be `html`.
3. The start tag of the root element of the document *must* explicitly contain a default namespace declaration for the XHTML namespace [XML-NAMES11 [p.59]]. The namespace URI for XHTML is defined to be `http://www.w3.org/1999/xhtml`.

The start tag *may* also contain the declaration of the XML Schema Instance Namespace and an XML Schema Instance `schemaLocation` attribute [XMLSCHEMA-2 [p.59]]. Such an attribute would associate the XHTML namespace `http://www.w3.org/1999/xhtml` with the XML Schema at the URI

`http://www.w3.org/MarkUp/SCHEMA/xhtml-rdfa-2.xsd`.

```
<html xmlns="http://www.w3.org/1999/xhtml" lang="en" xml:lang="en"
      xmlns:xsi="http://www.w3.org/2001/XMLSchema-instance"
      xsi:schemaLocation="http://www.w3.org/1999/xhtml
                          http://www.w3.org/MarkUp/SCHEMA/xhtml-rdfa-2.xsd">
```

4. There *should* be a `@version` attribute on the `html` element with the value "XHTML+RDFa 1.1".

```
<?xml version="1.0" encoding="UTF-8"?>
<html xmlns="http://www.w3.org/1999/xhtml"
      version="XHTML+RDFa 1.1"
      xmlns:xsi="http://www.w3.org/2001/XMLSchema-instance"
      xsi:schemaLocation="http://www.w3.org/1999/xhtml
                          http://www.w3.org/MarkUp/SCHEMA/xhtml-rdfa-2.xsd"
      lang="en"
      xml:lang="en">
<head>
  <title>Virtual Library</title>
</head>
```

```
<body>
<p>Moved to <a href="http://example.org/">example.org</a>.</p>
</body>
</html>
```

Note that in this example, the XML declaration is included. An XML declaration like the one above is not required in all XML documents. XHTML document authors *should* use XML declarations in all their documents. XHTML document authors *must* use an XML declaration when the character encoding of the document is other than the default UTF-8 or UTF-16 and no encoding is specified by a higher-level protocol.

XHTML+RDFa documents *should* be labeled with the Internet Media Type "application/xhtml+xml" as defined in [RFC3236 [p.59]]. For further information on using media types with XHTML family markup languages, see the informative note [XHTML-MEDIA-TYPES [p.60]].

2.2 User Agent Conformance

A conforming user agent *must* support all of the features required in this specification. A conforming user agent must also support the User Agent conformance requirements as defined in XHTML Modularization [XHTML-MODULARIZATION11-2e [p.59]] section on "XHTML Family User Agent Conformance".

3. Additional RDFa Processing Rules

Documents conforming to the rules in this specification are processed according to [RDFA-CORE [p.59]] with the following extensions:

- The default vocabulary URI is `http://www.w3.org/1999/xhtml/vocab#`.
- The default collection of terms is defined in XHTML Default Vocabulary Terms [p.13]
- The base can be set using the `base` element as defined in [XHTML-MODULARIZATION11-2e [p.59]].
- The current language can be set using either the `@lang` or `@xml:lang` attributes.
- In section 6.5, processing step 6, if no URI is provided by a resource attribute, then first check to see if the element is the `head` or `body` element. If it is, then act as if there is an empty `@about` present, and process it according to the rule for `@about`.
- In section 6.5, processing step 7, if no URI is provided, then first check to see if the element is the `head` or `body` element. If it is, then act as if there is an empty `@about` present, and process it according to the rule for `@about`.

4. XHTML+RDFa 1.1 Definition

The XHTML+RDFa 1.1 document type is a fully functional document type with rich semantics. It is a superset of [XHTML11-2e [p.59]].

The XHTML+RDFa 1.1 document type is made up of the following XHTML modules. The elements, attributes, and content models associated with these modules are defined in "XHTML Modularization" [XHTML-MODULARIZATION11-2e [p.59]]. The elements are listed here for information purposes, but the definitions in XHTML Modularization should be considered authoritative.

Structure Module

- body, head, html, title

Text Module

- abbr, acronym, address, blockquote, br, cite, code, dfn, div, em,
- h1, h2, h3, h4, h5, h6, kbd, p, pre, q, samp, span, strong, var

Hypertext Module

- a, and @href is available on all elements.

List Module

- dl, dt, dd, ol, ul, li

Object Module

- object, param

Presentation Module

- b, big, hr, i, small, sub, sup, tt

Edit Module

- del, ins

Bidirectional Text Module

- bdo

Forms Module

- button,fieldset,form,input,label,legend,select,optgroup,
- option,textarea

Table Module

- caption,col,colgroup,table,tbody,td,tfoot,th,thead,tr

Image Module

- img

Client-side Image Map Module

- area,map

Server-side Image Map Module

- Attribute ismap on img

Intrinsic Events Module

- Events attributes

Metainformation Module

- meta

Scripting Module

- noscript,script

Stylesheet Module

style element

Style Attribute Module *Deprecated*

@style

Target Module

@target

Link Module

link

Base Module

base

Metainformation Attributes Module [p.13]

@about, @content, @datatype, @typeof, @property, @rel, @resource, @rev, @vocab

XHTML+RDFa also uses the Ruby Annotation module as defined in [RUBY [p.59]]:

Ruby Annotation Module

ruby, rbc, rtc, rb, rt, rp

This specification also adds the lang attribute to the I18N attribute collection as defined in [XHTML-MODULARIZATION11-2e [p.59]]. The lang attribute is defined in [HTML401 [p.59]]. When this attribute and the xml:lang attribute are specified on the same element, the xml:lang attribute takes precedence. When both lang and xml:lang are specified on the same element, they *should* have the same value.

There are no additional definitions required by this document type. An implementation of this document type as an XML Schema is defined in Appendix D [p.??] , and as an XML DTD is defined in Appendix A [p.39] .

5. Metainformation Attributes Module

The Metainformation Attributes Module defines the `Metainformation` attribute collection. This collection allows elements to be annotated with metadata throughout an XHTML-family document. When this module is included in a markup language, this collection is added to the `Common` attribute collection as defined in [XHTML-MODULARIZATION11-2e [p.59]].

5.1 Metainformation Attributes Collection

The following attributes are included in the attribute collection, and take values in the associated datatype:

Attributes	Notes
about (URIorCURIE)	
content (CDATA)	
datatype (URIorCURIE)	If not specified, then the default value is <code>string</code> as defined in [XMLSCHEMA-2 [p.59]].
typeof (TERMorURIorCURIE)+	
prefix(NCName ': ' URI)+	
property (TERMorURIorCURIE)+	
rel (TERMorURIorCURIEs)	
resource (URIorCURIE)	
rev (TERMorURIorCURIEs)	
vocab URI	A URI that defines the prefix to use when a CURIE is specified with no prefix and no colon.

An implementation of this module in XML Schema can be found in Appendix A [p.17] and in XML DTD in Appendix B [p.39] .

5.2 XHTML Default Vocabulary Terms

Note that the values defined in this section may be removed from this document and placed in an external 'RDFa Profile' so that they can be maintained independent of the specification.

The terms defined in this section *must* be mapped to lower case by an RDFa Processor. The vocabulary terms are:

alternate

Designates alternate versions for a resource.

appendix

Refers to a resource serving as an appendix in a collection.

bookmark

Refers to a bookmark. A bookmark is a link to a key entry point within an extended document. The @title attribute may be used, for example, to label the bookmark. Note that several bookmarks may be defined for a document.

cite

Refers to a resource that defines a citation. In the following example, the `cite` is used to reference the book from which the quotation is taken:

```
As Gandalf the White said in
<span rel="cite" resource="http://www.example.com/books/the_two_towers">
    The Two Towers
</span>,
<quote xml:lang="en">"The hospitality of
your hall is somewhat lessened of late, Theoden King."</quote>
```

which would generate the following triples:

```
<> xv:cite <http://www.example.com/books/the_two_towers> .
```

`cite` is also useful for referencing specifications:

```
More information can be found in
<span rel="cite" resource="http://www.w3.org/TR/REC-xml">[XML]</cite>.
```

which would generate the following triples:

```
<> xv:cite <http://www.w3.org/TR/REC-xml> .
```

chapter

Refers to a resource serving as a chapter in a collection.

contents

Refers to a resource serving as a table of contents.

copyright

Refers to a copyright statement for the resource.

first

Refers to the first item in a collection (see also start and top).

glossary

Refers to a resource providing a glossary of terms.

help

Refers to a resource offering help (more information, links to other sources of information, etc.)

icon

Refers to a resource that represents an icon.

index

Refers to a resource providing an index.

last

Refers to the last resource in a collection of resources.

license

Refers to a resource that defines the license associated with a resource.

meta

Refers to a resource that provides metadata, for instance in RDF.

next

Refers to the next resource (after the current one) in an ordered collection.

p3pv1

Refers to a P3P Policy Reference File. See [[!P3P1.0]].

prev

Refers to the previous resource (before the current one) in an ordered collection.

role

Indicates the purpose of the resource. For some possible values, see [XHTML-VOCAB [p.60]].

section

Refers to a resource serving as a section in a collection.

stylesheet

Refers to a resource acting as a stylesheet for a resource.

subsection

Refers to a resource serving as a subsection in a collection.

start

Refers to the first resource in a collection of resources. A typical use case might be a collection of chapters in a book.

top

Synonym for start.

up

Refers to the resource "above" in a hierarchically structured set.

A. XHTML+RDFa XML Schema

This appendix is *normative*.

This appendix includes an implementation of the XHTML+RDFa 1.1 language using XML Schema. It is implemented by combining the XHTML 1.1 Schema with the XHTML Metainformation Attribute Module. This is done by using a content model module, and then a driver module. There are direct links to the various files, and the files are also contained in the "Gzip'd TAR" and "Zip" archives linked to at the top of this document. Please note that the files targeted by the "latest version" links may change slowly over time. See the W3C XHTML2 Working Group home page for more information.

A.1 XHTML Metainformation Attributes Module

You can download this version of this file from SCHEMA/xhtml-metaAttributes-2.xsd. The latest version is available at <http://www.w3.org/MarkUp/SCHEMA/xhtml-metaAttributes-2.xsd>.

```
<?xml version="1.0" encoding="UTF-8"?>
<xs:schema
    xmlns:xs="http://www.w3.org/2001/XMLSchema"
    xmlns:xh11d="http://www.w3.org/1999/xhtml/datatypes/"
    elementFormDefault="qualified"
>
  <xs:import namespace="http://www.w3.org/1999/xhtml/datatypes/"
    schemaLocation="xhtml-datatypes-1.xsd" />
  <xs:annotation>
    <xs:documentation>
      This is the XML Schema Metainformation Attributes module for XHTML

      $Id: Overview.html,v 1.12 2010/04/16 15:25:10 smccarro Exp $
    </xs:documentation>
    <xs:documentation source="xhtml-rdfa-copyright-1.xsd"/>
  </xs:annotation>

  <xs:annotation>
    <xs:documentation>
      XHTML Metainformation Attributes
    </xs:documentation>
  </xs:annotation>

  <xs:attribute name="about" type="xh11d:URIorCURIE"/>
  <xs:attribute name="content" type="xh11d:CDATA"/>
  <xs:attribute name="datatype" type="xh11d:TERMorURIorCURIE"/>
  <xs:attribute name="typeof" type="xh11d:TERMorURIorCURIES"/>
  <xs:attribute name="prefix" type="xh11d:PREFIX"/>
  <xs:attribute name="property" type="xh11d:TERMorURIorCURIES"/>
  <xs:attribute name="rel" type="xh11d:TERMorURIorCURIES"/>
  <xs:attribute name="resource" type="xh11d:URIorCURIE"/>
  <xs:attribute name="rev" type="xh11d:TERMorURIorCURIES"/>
  <xs:attribute name="vocab" type="xs:anyURI"/>

  <xs:attributeGroup name="xhtml.metaAttributes.attrib">
    <xs:attribute name="about" />
```

```

<xs:attribute name="content" />
<xs:attribute name="datatype" />
<xs:attribute name="typeof" />
<xs:attribute name="prefix" />
<xs:attribute name="property" />
<xs:attribute name="rel" />
<xs:attribute name="resource" />
<xs:attribute name="rev" />
<xs:attribute name="vocab" />
</xs:attributeGroup>
</xs:schema>

```

A.2 XHTML+RDFa Schema Content Model Module

You can download this version of this file from SCHEMA/xhtml-rdfa-model-2.xsd. The latest version is available at <http://www.w3.org/MarkUp/SCHEMA/xhtml-rdfa-model-2.xsd>.

```

<?xml version="1.0" encoding="UTF-8"?>
<xs:schema
  xmlns:xs="http://www.w3.org/2001/XMLSchema"
  xmlns:xh11d="http://www.w3.org/1999/xhtml/datatypes/"
  elementFormDefault="qualified" >
  <xs:import
    namespace="http://www.w3.org/1999/xhtml/datatypes/"
    schemaLocation="xhtml-datatypes-1.xsd"/>
  <xs:annotation>
    <xs:documentation>
      This is the XML Schema module of common content models for XHTML11
      $Id: Overview.html,v 1.12 2010/04/16 15:25:10 smccarro Exp $
    </xs:documentation>
    <xs:documentation source="xhtml-copyright-1.xsd"/>
  </xs:annotation>
  <xs:annotation>
    <xs:documentation>
      XHTML Document Model
      This module describes the groupings of elements/attributes
      that make up common content models for XHTML elements.
      XHTML has following basic content models:
      xhtml.Inline.mix; character-level elements
      xhtml.Block.mix; block-like elements, e.g., paragraphs and lists
      xhtml.Flow.mix; any block or inline elements
      xhtml.HeadOpts.mix; Head Elements
      xhtml.InlinePre.mix; Special class for pre content model
      xhtml.InlineNoAnchor.mix; Content model for Anchor
    </xs:documentation>
  </xs:annotation>
  Any groups declared in this module may be used to create
  element content models, but the above are considered 'global'
  (insofar as that term applies here). XHTML has the
  following Attribute Groups
    xhtml.Core.extra.attrib
    xhtml.I18n.extra.attrib
    xhtml.Common.extra

```

The above attribute Groups are considered Global

```

        </xs:documentation>
    </xs:annotation>
    <xs:include schemaLocation="xhtml-metaAttributes-2.xsd">
        <xs:annotation>
            <xs:documentation>
                XHTML Metainformation Modules

                Attributes defined here:
                XHTML RDFa attribtues
            </xs:documentation>
            <xs:annotation source="http://www.w3.org/TR/rdfa-syntax"/>
        </xs:annotation>
    </xs:include>
    <xs:attributeGroup
        name="xhtml.I18n.extra.attrib">
        <xs:annotation>
            <xs:documentation> Extended I18n attribute </xs:documentation>
        </xs:annotation>
        <xs:attributeGroup
            ref="xhtml.dir.attrib">
            <xs:annotation>
                <xs:documentation>
                    "dir" Attribute from Bi Directional Text (bdo) Module
                </xs:documentation>
            </xs:annotation>
        </xs:attributeGroup>
    </xs:attributeGroup>
    <xs:attributeGroup
        name="xhtml.Common.extra">
        <xs:annotation>
            <xs:documentation> Extended Common Attributes </xs:documentation>
        </xs:annotation>
        <xs:attributeGroup
            ref="xhtml.style.attrib">
            <xs:annotation>
                <xs:documentation>
                    "style" attribute from Inline Style Module
                </xs:documentation>
            </xs:annotation>
        </xs:attributeGroup>
    </xs:attributeGroup>
    <xs:attributeGroup ref="xhtml.Events.attrib">
        <xs:annotation>
            <xs:documentation>
                Attributes from Events Module
            </xs:documentation>
        </xs:annotation>
    </xs:attributeGroup>
    <xs:attributeGroup ref="xhtml.metaAttributes.attrib">
        <xs:annotation>
            <xs:documentation>
                Attributes from Metainformation Module
            </xs:documentation>
        </xs:annotation>
    </xs:attributeGroup>
    <xs:attributeGroup
        name="xhtml.Core.extra.attrib">

```

```

<xs:annotation>
  <xs:documentation> Extend Core Attributes </xs:documentation>
</xs:annotation>
</xs:attributeGroup>
<xs:attributeGroup
  name="xhtml.Global.core.extra.attrib">
  <xs:annotation>
    <xs:documentation> Extended Global Core Attributes </xs:documentation>
  </xs:annotation>
</xs:attributeGroup>
<xs:attributeGroup
  name="xhtml.Global.I18n.extra.attrib">
  <xs:annotation>
    <xs:documentation> Extended Global I18n attributes </xs:documentation>
  </xs:annotation>
</xs:attributeGroup>
<xs:attributeGroup
  name="xhtml.Global.Common.extra">
  <xs:annotation>
    <xs:documentation> Extended Global Common Attributes </xs:documentation>
  </xs:annotation>
</xs:attributeGroup>
<xs:group
  name="xhtml.Head.extra">
  <xs:sequence/>
</xs:group>
<xs:group
  name="xhtml.HeadOpts.mix">
  <xs:choice>
    <xs:element name="script"
      type="xhtml.script.type"/>
    <xs:element name="style"
      type="xhtml.style.type"/>
    <xs:element name="meta"
      type="xhtml.meta.type"/>
    <xs:element name="link"
      type="xhtml.link.type"/>
    <xs:element name="object"
      type="xhtml.object.type"/>
    <xs:group
      ref="xhtml.Head.extra"/>
  </xs:choice>
</xs:group>
<xs:group
  name="xhtml.head.content">
  <xs:sequence>
    <xs:group
      ref="xhtml.HeadOpts.mix"
      minOccurs="0"
      maxOccurs="unbounded"/>
    <xs:choice>
      <xs:sequence>
        <xs:element name="title"
          minOccurs="1"
          maxOccurs="1"
          type="xhtml.title.type"/>
        <xs:group>

```

```

        ref="xhtml.HeadOpts.mix"
        minOccurs="0"
        maxOccurs="unbounded"/>
    <xs:sequence
        minOccurs="0">
        <xs:element name="base"
            type="xhtml.base.type"/>
        <xs:group
            ref="xhtml.HeadOpts.mix"
            minOccurs="0"
            maxOccurs="unbounded"/>
    </xs:sequence>
</xs:sequence>
<xs:sequence>
    <xs:element name="base"
        type="xhtml.base.type"
        minOccurs="1"
        maxOccurs="1"/>
    <xs:group
        ref="xhtml.HeadOpts.mix"
        minOccurs="0"
        maxOccurs="unbounded"/>
    <xs:element name="title"
        minOccurs="1"
        maxOccurs="1"
        type="xhtml.title.type"/>
    <xs:group
        ref="xhtml.HeadOpts.mix"
        minOccurs="0"
        maxOccurs="unbounded"/>
</xs:sequence>
</xs:choice>
</xs:sequence>
</xs:group>
<!--
ins and del are used to denote editing changes
-->
<xs:group
    name="xhtml.Edit.class">
    <xs:choice>
        <xs:element name="ins"
            type="xhtml.edit.type"/>
        <xs:element name="del"
            type="xhtml.edit.type"/>
    </xs:choice>
</xs:group>
<!--
script and noscript are used to contain scripts
and alternative content
-->
<xs:group
    name="xhtml.Script.class">
    <xs:choice>
        <xs:element name="script"
            type="xhtml.script.type"/>
        <xs:element name="noscript"
            type="xhtml.noscript.type"/>
    </xs:choice>
</xs:group>

```

```

        </xs:choice>
    </xs:group>
    <xs:group
        name="xhtml.Misc.extra">
        <xs:sequence/>
    </xs:group>
    <!--
    These elements are neither block nor inline, and can
    essentially be used anywhere in the document body.
-->
    <xs:group
        name="xhtml.Misc.class">
        <xs:choice>
            <xs:group
                ref="xhtml.Edit.class"/>
            <xs:group
                ref="xhtml.Script.class"/>
            <xs:group
                ref="xhtml.Misc.extra"/>
        </xs:choice>
    </xs:group>
    <!-- Inline Elements -->
    <xs:group
        name="xhtml.InlStruct.class">
        <xs:choice>
            <xs:element name="br"
                type="xhtml.br.type"/>
            <xs:element name="span"
                type="xhtml.span.type"/>
        </xs:choice>
    </xs:group>
    <xs:group
        name="xhtml.InlPhras.class">
        <xs:choice>
            <xs:element name="em"
                type="xhtml.em.type"/>
            <xs:element name="strong"
                type="xhtml.strong.type"/>
            <xs:element name="dfn"
                type="xhtml.dfn.type"/>
            <xs:element name="code"
                type="xhtml.code.type"/>
            <xs:element name="samp"
                type="xhtml.samp.type"/>
            <xs:element name="kbd"
                type="xhtml.kbd.type"/>
            <xs:element name="var"
                type="xhtml.var.type"/>
            <xs:element name="cite"
                type="xhtml.cite.type"/>
            <xs:element name="abbr"
                type="xhtml.abbr.type"/>
            <xs:element name="acronym"
                type="xhtml.acronym.type"/>
            <xs:element name="q"
                type="xhtml.q.type"/>
        </xs:choice>
    </xs:group>

```

```

</xs:group>
<xs:group
  name="xhtml.InlPres.class">
  <xs:choice>
    <xs:element name="tt"
      type="xhtml.InlPres.type"/>
    <xs:element name="i"
      type="xhtml.InlPres.type"/>
    <xs:element name="b"
      type="xhtml.InlPres.type"/>
    <xs:element name="big"
      type="xhtml.InlPres.type"/>
    <xs:element name="small"
      type="xhtml.InlPres.type"/>
    <xs:element name="sub"
      type="xhtml.InlPres.type"/>
    <xs:element name="sup"
      type="xhtml.InlPres.type"/>
  </xs:choice>
</xs:group>
<xs:group
  name="xhtml.I18n.class">
  <xs:sequence>
    <xs:element name="bdo"
      type="xhtml.bdo.type"/>
  </xs:sequence>
</xs:group>
<xs:group
  name="xhtml.Anchor.class">
  <xs:sequence>
    <xs:element name="a"
      type="xhtml.a.type"/>
  </xs:sequence>
</xs:group>
<xs:group
  name="xhtml.InlSpecial.class">
  <xs:choice>
    <xs:element name="img"
      type="xhtml.img.type"/>
    <xs:element name="map"
      type="xhtml.map.type"/>
    <xs:element name="object"
      type="xhtml.object.type"/>
  </xs:choice>
</xs:group>
<xs:group
  name="xhtml.InlForm.class">
  <xs:choice>
    <xs:element name="input"
      type="xhtml.input.type"/>
    <xs:element name="select"
      type="xhtml.select.type"/>
    <xs:element name="textarea"
      type="xhtml.textarea.type"/>
    <xs:element name="label"
      type="xhtml.label.type"/>
    <xs:element name="button"
      type="xhtml.button.type"/>
  </xs:choice>
</xs:group>

```

```

        type="xhtml.button.type" />
    </xs:choice>
</xs:group>
<xs:group
    name="xhtml.Inline.extra">
    <xs:sequence/>
</xs:group>
<xs:group
    name="xhtml.Ruby.class">
    <xs:sequence>
        <xs:element name="ruby"
            type="xhtml.ruby.type"/>
    </xs:sequence>
</xs:group>
<!--
Inline.class includes all inline elements,
used as a component in mixes
-->
<xs:group
    name="xhtml.Inline.class">
    <xs:choice>
        <xs:group
            ref="xhtml.InlStruct.class"/>
        <xs:group
            ref="xhtml.InlPhras.class"/>
        <xs:group
            ref="xhtml.InlPres.class"/>
        <xs:group
            ref="xhtml.I18n.class"/>
        <xs:group
            ref="xhtml.Anchor.class"/>
        <xs:group
            ref="xhtml.InlSpecial.class"/>
        <xs:group
            ref="xhtml.InlForm.class"/>
        <xs:group
            ref="xhtml.Ruby.class"/>
        <xs:group
            ref="xhtml.Inline.extra"/>
    </xs:choice>
</xs:group>
<!--
InlNoRuby.class includes all inline elements
except ruby
-->
<xs:group
    name="xhtml.InlNoRuby.class">
    <xs:choice>
        <xs:group
            ref="xhtml.InlStruct.class"/>
        <xs:group
            ref="xhtml.InlPhras.class"/>
        <xs:group
            ref="xhtml.InlPres.class"/>
        <xs:group
            ref="xhtml.I18n.class"/>
        <xs:group

```

```

        ref="xhtml.Anchor.class"/>
<xs:group
    ref="xhtml.InlSpecial.class"/>
<xs:group
    ref="xhtml.InlForm.class"/>
<xs:group
    ref="xhtml.Inline.extra"/>
</xs:choice>
</xs:group>
<!--
InlinePre.mix
Used as a component in pre model
-->
<xs:group
    name="xhtml.InlinePre.mix">
<xs:choice>
    <xs:group
        ref="xhtml.InlStruct.class"/>
    <xs:group
        ref="xhtml.InlPhras.class"/>
    <xs:element name="tt"
        type="xhtml.InlPres.type"/>
    <xs:element name="i"
        type="xhtml.InlPres.type"/>
    <xs:element name="b"
        type="xhtml.InlPres.type"/>
    <xs:group
        ref="xhtml.I18n.class"/>
    <xs:group
        ref="xhtml.Anchor.class"/>
    <xs:group
        ref="xhtml.Misc.class"/>
    <xs:element name="map"
        type="xhtml.map.type"/>
    <xs:group
        ref="xhtml.Inline.extra"/>
</xs:choice>
</xs:group>
<!--
InlNoAnchor.class includes all non-anchor inlines,
used as a component in mixes
-->
<xs:group
    name="xhtml.InlNoAnchor.class">
<xs:choice>
    <xs:group
        ref="xhtml.InlStruct.class"/>
    <xs:group
        ref="xhtml.InlPhras.class"/>
    <xs:group
        ref="xhtml.InlPres.class"/>
    <xs:group
        ref="xhtml.I18n.class"/>
    <xs:group
        ref="xhtml.InlSpecial.class"/>
    <xs:group
        ref="xhtml.InlForm.class"/>

```

```

<xs:group
    ref="xhtml.Ruby.class"/>
<xs:group
    ref="xhtml.Inline.extra"/>
</xs:choice>
</xs:group>
<!--
InlNoAnchor.mix includes all non-anchor inlines
-->
<xs:group
    name="xhtml.InlNoAnchor.mix">
<xs:choice>
    <xs:group
        ref="xhtml.InlNoAnchor.class"/>
    <xs:group
        ref="xhtml.Misc.class"/>
</xs:choice>
</xs:group>
<!--
Inline.mix includes all inline elements, including Misc.class
-->
<xs:group
    name="xhtml.Inline.mix">
<xs:choice>
    <xs:group
        ref="xhtml.Inline.class"/>
    <xs:group
        ref="xhtml.Misc.class"/>
</xs:choice>
</xs:group>
<!--
InlNoRuby.mix includes all of inline.mix elements
except ruby
-->
<xs:group
    name="xhtml.InlNoRuby.mix">
<xs:choice>
    <xs:group
        ref="xhtml.InlNoRuby.class"/>
    <xs:group
        ref="xhtml.Misc.class"/>
</xs:choice>
</xs:group>
<!--
In the HTML 4 DTD, heading and list elements were included
in the block group. The Heading.class and
List.class groups must now be included explicitly
on element declarations where desired.
-->
<xs:group
    name="xhtml.Heading.class">
<xs:choice>
    <xs:element name="h1"
        type="xhtml.h1.type"/>
    <xs:element name="h2"
        type="xhtml.h2.type"/>
    <xs:element name="h3"
        type="xhtml.h3.type"/>
</xs:choice>
</xs:group>

```

```

        type="xhtml.h3.type"/>
<xs:element name="h4"
        type="xhtml.h4.type"/>
<xs:element name="h5"
        type="xhtml.h5.type"/>
<xs:element name="h6"
        type="xhtml.h6.type"/>
</xs:choice>
</xs:group>
<xs:group
    name="xhtml.List.class">
<xs:choice>
    <xs:element name="ul"
        type="xhtml.ul.type"/>
    <xs:element name="ol"
        type="xhtml.ol.type"/>
    <xs:element name="dl"
        type="xhtml.dl.type"/>
</xs:choice>
</xs:group>
<xs:group
    name="xhtml.Table.class">
<xs:choice>
    <xs:element name="table"
        type="xhtml.table.type"/>
</xs:choice>
</xs:group>
<xs:group
    name="xhtml.Form.class">
<xs:choice>
    <xs:element name="form"
        type="xhtml.form.type"/>
</xs:choice>
</xs:group>
<xs:group
    name="xhtml.Fieldset.class">
<xs:choice>
    <xs:element name="fieldset"
        type="xhtml.fieldset.type"/>
</xs:choice>
</xs:group>
<xs:group
    name="xhtml.BlkStruct.class">
<xs:choice>
    <xs:element name="p"
        type="xhtml.p.type"/>
    <xs:element name="div"
        type="xhtml.div.type"/>
</xs:choice>
</xs:group>
<xs:group
    name="xhtml.BlkPhras.class">
<xs:choice>
    <xs:element name="pre"
        type="xhtml.pre.type"/>
    <xs:element name="blockquote"
        type="xhtml.blockquote.type"/>

```

```

<xs:element name="address"
            type="xhtml.address.type" />
        </xs:choice>
    </xs:group>
    <xs:group
        name="xhtml.BlkPres.class">
        <xs:sequence>
            <xs:element name="hr"
                        type="xhtml.hr.type" />
        </xs:sequence>
    </xs:group>
    <xs:group
        name="xhtml.BlkSpecial.class">
        <xs:choice>
            <xs:group
                ref="xhtml.Table.class" />
            <xs:group
                ref="xhtml.Form.class" />
            <xs:group
                ref="xhtml.Fieldset.class" />
        </xs:choice>
    </xs:group>
    <xs:group
        name="xhtml.Block.extra">
        <xs:sequence/>
    </xs:group>
<!--
Block.class includes all block elements,
used as an component in mixes
-->
    <xs:group
        name="xhtml.Block.class">
        <xs:choice>
            <xs:group
                ref="xhtml.BlkStruct.class" />
            <xs:group
                ref="xhtml.BlkPhras.class" />
            <xs:group
                ref="xhtml.BlkPres.class" />
            <xs:group
                ref="xhtml.BlkSpecial.class" />
            <xs:group
                ref="xhtml.Block.extra" />
        </xs:choice>
    </xs:group>
<!--
Block.mix includes all block elements plus %Misc.class;
-->
    <xs:group
        name="xhtml.Block.mix">
        <xs:choice>
            <xs:group
                ref="xhtml.Heading.class" />
            <xs:group
                ref="xhtml.List.class" />
            <xs:group
                ref="xhtml.Block.class" />

```

```

<xs:group
    ref="xhtml.Misc.class"/>
</xs:choice>
</xs:group>
<!--
All Content Elements
Flow.mix includes all text content, block and inline
Note that the "any" element included here allows us
to add data from any other namespace, a necessity
for compound document creation.
Note however that it is not possible to add
to any head level element without further
modification. To add RDF metadata to the head
of a document, modify the structure module.
-->
<xs:group
    name="xhtml.Flow.mix">
    <xs:choice>
        <xs:group
            ref="xhtml.Heading.class"/>
        <xs:group
            ref="xhtml.List.class"/>
        <xs:group
            ref="xhtml.Block.class"/>
        <xs:group
            ref="xhtml.Inline.class"/>
        <xs:group
            ref="xhtml.Misc.class"/>
    </xs:choice>
</xs:group>
<!--
BlkNoForm.mix includes all non-form block elements,
plus Misc.class
-->
<xs:group
    name="xhtml.BlkNoForm.mix">
    <xs:choice>
        <xs:group
            ref="xhtml.Heading.class"/>
        <xs:group
            ref="xhtml.List.class"/>
        <xs:group
            ref="xhtml.BlkStruct.class"/>
        <xs:group
            ref="xhtml.BlkPhras.class"/>
        <xs:group
            ref="xhtml.BlkPres.class"/>
        <xs:group
            ref="xhtml.Table.class"/>
        <xs:group
            ref="xhtml.Block.extra"/>
        <xs:group
            ref="xhtml.Misc.class"/>
    </xs:choice>
</xs:group>

```

```

</xs:group>
<xs:element name="html"
    type="xhtml.html.type"/>
</xs:schema>

```

A.3 XHTML+RDFa Schema Modules

You can download this version of this file from SCHEMA/xhtml-rdfa-modules-2.xsd. The latest version is available at <http://www.w3.org/MarkUp/SCHEMA/xhtml-rdfa-modules-2.xsd>.

```

<?xml version="1.0" encoding="UTF-8"?>
<xs:schema xmlns:xs="http://www.w3.org/2001/XMLSchema"
    elementFormDefault="qualified"
    xmlns:xh1d="http://www.w3.org/1999/xhtml/datatypes/">
    <xs:import namespace="http://www.w3.org/1999/xhtml/datatypes/"
        schemaLocation="xhtml-datatypes-1.xsd" />
    <xs:import namespace="http://www.w3.org/XML/1998/namespace"
        schemaLocation="http://www.w3.org/2001/xml.xsd" />
    <xs:annotation>
        <xs:documentation>
            This schema includes all modules for XHTML1.1 Document Type.
            $Id: Overview.html,v 1.12 2010/04/16 15:25:10 smccarro Exp $
        </xs:documentation>
        <xs:documentation source="xhtml-copyright-1.xsd"/>
    </xs:annotation>
    <xs:annotation>
        <xs:documentation>
            This schema includes all modules (and redefinitions)
            for XHTML1.1 Document Type.
            XHTML1.1 Document Type includes the following Modules
        </xs:documentation>
        XHTML Core modules (Required for XHTML Family Conformance)
        +
        text
        +
        hypertext
        +
        lists
        +
        structure
    </xs:annotation>
    Other XHTML modules
    +
    Edit
    +
    Bdo
    +
    Presentational
    +
    Link
    +
    Meta
    +
    Base
    +
    Scripting
    +
    Style
    +
    Image
    +
    Applet
    +
    Object
    +
    Param (Applet/Object modules require Param Module)
    +
    Tables
    +
    Target
    +
    Forms
    +
    Client side image maps
    +
    Server side image maps
</xs:annotation>
</xs:documentation>
</xs:annotation>
<xs:include schemaLocation="xhtml-framework-1.xsd">
    <xs:annotation>
        <xs:documentation>
            Schema Framework Component Modules:
            +
            notations
            +
            datatypes
            +
            common attributes
            +
            character entities
        </xs:documentation>
        <xs:documentation source="http://www.w3.org/TR/xhtml-modularization/abstract_modules.html#s_commonatts"/>
    </xs:annotation>
</xs:include>
<xs:include schemaLocation="xhtml-text-1.xsd">
    <xs:annotation>
        <xs:documentation>
            Text module
        </xs:documentation>
        The Text module includes declarations for all core
        text container elements and their attributes.
        +
        block phrasal
        +
        block structural
        +
        inline phrasal
        +
        inline structural
    </xs:annotation>
    Elements defined here:
    *
    address, blockquote, pre, h1, h2, h3, h4, h5, h6
    *
    div, p
    *
    abbr, acronym, cite, code, dfn, em, kbd, q, samp, strong, var

```

```

        * br, span
    </xs:documentation>
    <xs:documentation source="http://www.w3.org/TR/2001/REC-xhtml-modularization-20010410/abstract_modules.html#s_textmodule"/>
    </xs:annotation>
</xs:include>

<xs:include schemaLocation="xhtml-list-1.xsd">
    <xs:annotation>
        <xs:documentation>
Lists module

Elements defined here:
    * dt, dd, dl, ol, ul, li
    </xs:documentation>
    <xs:documentation source="http://www.w3.org/TR/2001/REC-xhtml-modularization-20010410/abstract_modules.html#s_listmodule"/>
    </xs:annotation>
</xs:include>
<xs:redefine schemaLocation="xhtml-struct-1.xsd">
    <xs:annotation>
        <xs:documentation>
Structural module

Elements defined here:
    * title, head, body, html
    </xs:documentation>
    <xs:documentation source="http://www.w3.org/TR/2001/REC-xhtml-modularization-20010410/abstract_modules.html#s_structurerule"/>
    </xs:annotation>
    <xs:attributeGroup name="xhtml.version.attrib">
        <xs:annotation>
            <xs:documentation>
Redefinition by the XHTML11 Markup (for value of version attr)
            </xs:documentation>
        </xs:annotation>
        <xs:attribute name="version" type="xh11:CDATA" fixed="XHTML+RDFa 1.0"/>
    </xs:attributeGroup>
    <xs:attributeGroup name="xhtml.body.attlist">
        <xs:attributeGroup ref="xhtml.body.attlist">
            <xs:annotation>
                <xs:documentation>
Original Body Attlist
                </xs:documentation>
            </xs:annotation>
        </xs:attributeGroup>
        <xs:attributeGroup ref="xhtml.body.events.attlist">
            <xs:annotation>
                <xs:documentation>
Redefinition by XHTML Event Attribute Module
                </xs:documentation>
            </xs:annotation>
        </xs:attributeGroup>
        <xs:attributeGroup name="xhtml.head.attlist">
            <xs:attributeGroup ref="xhtml.head.attlist"/>
            <xs:attributeGroup ref="xhtml.class"/>
            <xs:attributeGroup ref="xhtml.title"/>
            <xs:attributeGroup ref="xhtml.Common.extra"/>
        </xs:attributeGroup>
        <xs:attributeGroup name="xhtml.title.attlist">
            <xs:attributeGroup ref="xhtml.title.attlist"/>
            <xs:attributeGroup ref="xhtml.class"/>
            <xs:attributeGroup ref="xhtml.title"/>
            <xs:attributeGroup ref="xhtml.Common.extra"/>
        </xs:attributeGroup>
    </xs:attributeGroup>
    <xs:include schemaLocation="xhtml-edit-1.xsd">
        <xs:annotation>
            <xs:documentation>
Edit module

Elements defined here:
    * ins, del
            </xs:documentation>
            <xs:documentation source="http://www.w3.org/TR/xhtml-modularization/abstract_modules.html#s_editmodule"/>
        </xs:annotation>
</xs:include>
<xs:include schemaLocation="xhtml-bdo-1.xsd">
    <xs:annotation>
        <xs:documentation>
Bidirectional element module

Elements defined here:
    * bdo
    </xs:documentation>
    <xs:documentation source="http://www.w3.org/TR/xhtml-modularization/abstract_modules.html#s_bdomodule"/>
</xs:annotation>
<xs:include schemaLocation="xhtml-pres-1.xsd">
    <xs:annotation>
        <xs:documentation>
Presentational module

Elements defined here:
    * hr, b, big, i, small,sub, sup, tt
    </xs:documentation>
    <xs:documentation source="http://www.w3.org/TR/xhtml-modularization/abstract_modules.html#s_presentationmodule"/>
</xs:annotation>

```

```

</xs:include>
<xs:redefine schemaLocation="xhtml-base-1.xsd">
  <xs:annotation>
    <xs:documentation>
      Base module

      Elements defined here:
      * base
    </xs:documentation>
    <xs:documentation source="http://www.w3.org/TR/xhtml-modularization/abstract_modules.html#s_basemodule"/>
  </xs:annotation>
  <xs:attributeGroup name="xhtml.base.attlist">
    <xs:annotation>
      <xs:documentation>
        Changes to XHTML base Attlist
      </xs:documentation>
    </xs:annotation>
    <xs:attributeGroup ref="xhtml.base.attlist">
      <xs:annotation>
        <xs:documentation>
          Original Base Attributes (declared in Base Module)
        </xs:documentation>
      </xs:annotation>
    </xs:attributeGroup>
    <xs:attributeGroup ref="xhtml.base.target.attlist">
      <xs:annotation>
        <xs:documentation>
          XHTML Target Module - Attribute additions
        </xs:documentation>
      </xs:annotation>
    </xs:attributeGroup>
  </xs:attributeGroup>
</xs:redefine>
<xs:include schemaLocation="xhtml-script-1.xsd">
  <xs:annotation>
    <xs:documentation>
      Scripting module

      Elements defined here:
      * script, noscript
    </xs:documentation>
    <xs:documentation source="http://www.w3.org/TR/xhtml-modularization/abstract_modules.html#s_scriptmodule"/>
  </xs:annotation>
</xs:include>
<xs:include schemaLocation="xhtml-style-1.xsd">
  <xs:annotation>
    <xs:documentation>
      Style module

      Elements defined here:
      * style
    </xs:documentation>
    <xs:documentation source="http://www.w3.org/TR/xhtml-modularization/abstract_modules.html#s_stylemodule"/>
  </xs:annotation>
</xs:include>
<xs:include schemaLocation="xhtml-inlstyle-1.xsd">
  <xs:annotation>
    <xs:documentation>
      Style attribute module

      Attribute defined here:
      * style
    </xs:documentation>
    <xs:documentation source="http://www.w3.org/TR/xhtml-modularization/abstract_modules.html#s_styleattributemode"/>
  </xs:annotation>
</xs:include>
<xs:redefine schemaLocation="xhtml-image-1.xsd">
  <xs:annotation>
    <xs:documentation>
      Image module

      Elements defined here:
      * img
    </xs:documentation>
    <xs:documentation source="http://www.w3.org/TR/xhtml-modularization/abstract_modules.html#s_imagemodule"/>
  </xs:annotation>
  <xs:attributeGroup name="xhtml.img.attlist">
    <xs:attributeGroup ref="xhtml.img.attlist">
      <xs:annotation>
        <xs:documentation>
          Original Image Attributes (in Image Module)
        </xs:documentation>
      </xs:annotation>
    </xs:attributeGroup>
    <xs:attributeGroup ref="xhtml.img.csim.attlist">
      <xs:annotation>
        <xs:documentation>
          Redefinition by Client Side Image Map Module
        </xs:documentation>
      </xs:annotation>
    </xs:attributeGroup>
    <xs:attributeGroup ref="xhtml.img.ssimap.attlist">
      <xs:annotation>
        <xs:documentation>
          Redefinition by Server Side Image Module
        </xs:documentation>
      </xs:annotation>
    </xs:attributeGroup>
  </xs:attributeGroup>
</xs:redefine>

```

```

        </xs:annotation>
    </xs:attributeGroup>
</xs:attributeGroup>
</xs:redefine>
<xs:redefine schemaLocation="xhtml-csismap-1.xsd">
    <xs:annotation>
        <xs:documentation>
            Client-side mage maps module
        </xs:documentation>
    </xs:annotation>
    Elements defined here:
        * area, map
</xs:redefine>
<xs:documentation source="http://www.w3.org/TR/xhtml-modularization/abstract_modules.html#s_imapmodule"/>
<xs:annotation>
<xs:attributeGroup name="xhtml.area.attlist">
    <xs:attributeGroup ref="xhtml.area.attlist">
        <xs:annotation>
            <xs:documentation>
                Original Area Attributes (in CSI Module)
            </xs:documentation>
        </xs:annotation>
    </xs:attributeGroup>
    <xs:attributeGroup ref="xhtml.area.events.attlist">
        <xs:annotation>
            <xs:documentation>
                Redefinition by Events Attribute Module
            </xs:documentation>
        </xs:annotation>
    </xs:attributeGroup>
    <xs:attributeGroup ref="xhtml.area.target.attlist">
        <xs:annotation>
            <xs:documentation>
                Target Module - Area Attribute Additions
            </xs:documentation>
        </xs:annotation>
    </xs:attributeGroup>
    <xs:attributeGroup>
        <xs:annotation>
            <xs:documentation>
                Server-side image maps module
            </xs:documentation>
        </xs:annotation>
    </xs:attributeGroup>
</xs:redefine>
<xs:include schemaLocation="xhtml-ssismap-1.xsd">
    <xs:annotation>
        <xs:documentation>
            Server-side image maps module
        </xs:documentation>
    </xs:annotation>
    Attributes defined here:
        * ismap on img
</xs:redefine>
<xs:include schemaLocation="xhtml-object-1.xsd">
    <xs:annotation>
        <xs:documentation>
            Object module
        </xs:documentation>
    </xs:annotation>
    Elements defined here:
        * object
</xs:redefine>
<xs:include schemaLocation="xhtml-param-1.xsd">
    <xs:annotation>
        <xs:documentation>
            Param module
        </xs:documentation>
    </xs:annotation>
    Elements defined here:
        * param
</xs:redefine>
<xs:include schemaLocation="xhtml-table-1.xsd">
    <xs:annotation>
        <xs:documentation>
            Tables module
        </xs:documentation>
    </xs:annotation>
    Elements defined here:
        * table, caption, thead, tfoot, tbody, colgroup, col, tr, th, td
</xs:redefine>
<xs:include schemaLocation="xhtml-modularization-abstract_modules.html#s_tablemodule"/>
</xs:annotation>

```

```

</xs:include>
<xs:redefine schemaLocation="xhtml-form-1.xsd">
  <xs:annotation>
    <xs:documentation>
      Forms module

      Elements defined here:
      * form, label, input, select, optgroup, option,
      * textarea, fieldset, legend, button
    </xs:documentation>
  </xs:annotation>
  <xs:documentation source="http://www.w3.org/TR/xhtml-modularization/abstract_modules.html#s_extformsmodule"/>
</xs:redefine>
<x:attributeGroup name="xhtml.form.attlist">
  <xs:annotation>
    <xs:documentation>
      Changes to XHTML Form Attlist
    </xs:documentation>
  </xs:annotation>
  <xs:attributeGroup ref="xhtml.form.attlist">
    <xs:annotation>
      <xs:documentation>
        Original Form Attributes (declared in Forms Module)
      </xs:documentation>
    </xs:annotation>
  </xs:attributeGroup>
  <xs:attributeGroup ref="xhtml.form.events.attlist">
    <xs:annotation>
      <xs:documentation>
        XHTML Events Module - Attribute additions
      </xs:documentation>
    </xs:annotation>
  </xs:attributeGroup>
  <xs:attributeGroup ref="xhtml.form.target.attlist">
    <xs:annotation>
      <xs:documentation>
        XHTML Target Module - Attribute additions
      </xs:documentation>
    </xs:annotation>
  </xs:attributeGroup>
  <xs:attributeGroup name="xhtml.input.attlist">
    <xs:annotation>
      <xs:documentation>
        Changes to XHTML Form Input Element
      </xs:documentation>
    </xs:annotation>
    <xs:attributeGroup ref="xhtml.input.attlist">
      <xs:annotation>
        <xs:documentation>
          Original Input Attributes (in Forms Module)
        </xs:documentation>
      </xs:annotation>
    </xs:attributeGroup>
    <xs:attributeGroup ref="xhtml.input.csim.attlist">
      <xs:annotation>
        <xs:documentation>
          Redefinition by Client Side Image Map Module
        </xs:documentation>
      </xs:annotation>
    </xs:attributeGroup>
    <xs:attributeGroup ref="xhtml.input.ssimap.attlist">
      <xs:annotation>
        <xs:documentation>
          Redefinition by Server Side Image Map Module
        </xs:documentation>
      </xs:annotation>
    </xs:attributeGroup>
    <xs:attributeGroup ref="xhtml.input.events.attlist">
      <xs:annotation>
        <xs:documentation>
          Redefinition by Event Attribute Module
        </xs:documentation>
      </xs:annotation>
    </xs:attributeGroup>
  </xs:attributeGroup>
  <xs:attributeGroup name="xhtml.label.attlist">
    <xs:attributeGroup ref="xhtml.label.attlist">
      <xs:annotation>
        <xs:documentation>
          Original Label Attributes (in Forms Module)
        </xs:documentation>
      </xs:annotation>
    </xs:attributeGroup>
    <xs:attributeGroup ref="xhtml.label.events.attlist">
      <xs:annotation>
        <xs:documentation>
          Redefinition by Event Attribute Module
        </xs:documentation>
      </xs:annotation>
    </xs:attributeGroup>
  </xs:attributeGroup>
  <xs:attributeGroup name="xhtml.select.attlist">
    <xs:attributeGroup ref="xhtml.select.attlist">
      <xs:annotation>
        <xs:documentation>
          Original Select Attributes (in Forms Module)
        </xs:documentation>
      </xs:annotation>
    </xs:attributeGroup>
  </xs:attributeGroup>
</xs:redefine>

```

```

</xs:documentation>
</xs:annotation>
</xs:attributeGroup>
<xs:attributeGroup ref="xhtml.select.events.attlist">
  <xs:annotation>
    <xs:documentation>
      Redefinition by Event Attribute Module
    </xs:documentation>
    </xs:annotation>
  </xs:attributeGroup>
</xs:attributeGroup>
<xs:attributeGroup name="xhtml.textarea.attlist">
  <xs:annotation ref="xhtml.textarea.attlist">
    <xs:annotation>
      <xs:documentation>
        Original TextArea Attributes (in Forms Module)
      </xs:documentation>
    </xs:annotation>
  </xs:attributeGroup>
<xs:attributeGroup ref="xhtml.textarea.events.attlist">
  <xs:annotation>
    <xs:documentation>
      Redefinition by Event Attribute Module
    </xs:documentation>
    </xs:annotation>
  </xs:attributeGroup>
</xs:attributeGroup>
<xs:attributeGroup name="xhtml.button.attlist">
  <xs:annotation ref="xhtml.button.attlist">
    <xs:annotation>
      <xs:documentation>
        Original Button Attributes (in Forms Module)
      </xs:documentation>
    </xs:annotation>
  </xs:attributeGroup>
<xs:attributeGroup ref="xhtml.button.events.attlist">
  <xs:annotation>
    <xs:documentation>
      Redefinition by Event Attribute Module
    </xs:documentation>
    </xs:annotation>
  </xs:attributeGroup>
</xs:attributeGroup>
</xs:redefine>
<xs:include schemaLocation="xhtml-ruby-basic-1.xsd">
  <xs:annotation>
    <xs:documentation>
      Ruby module
    </xs:documentation>
  </xs:annotation>
  Elements defined here:
  * ruby, rbc, rtc, rb, rt, rp
  Note that either Ruby or Basic Ruby should be used but not both
  </xs:documentation>
  <xs:documentation source="http://www.w3.org/TR/2001/REC-ruby-20010531/#simple-ruby1"/>
  </xs:annotation>
</xs:include>
<xs:include schemaLocation="xhtml-events-1.xsd">
  <xs:annotation>
    <xs:documentation>
      XHTML Events Modules
    </xs:documentation>
  </xs:annotation>
  Attributes defined here:
  XHTML Event Types
  </xs:documentation>
  <xs:documentation source="http://www.w3.org/TR/xhtml-modularization/abstract_modules.html#s_intrinsicseventsmodule"/>
  </xs:annotation>
</xs:include>
<xs:include schemaLocation="xhtml-metaAttributes-1.xsd">
  <xs:annotation>
    <xs:documentation>
      XHTML Metainformation Modules
    </xs:documentation>
  </xs:annotation>
  Attributes defined here:
  XHTML RDFa attribtues
  </xs:documentation>
  <xs:documentation source="http://www.w3.org/TR/rdfa-syntax"/>
  </xs:annotation>
</xs:include>
<xs:include schemaLocation="xhtml-target-1.xsd">
  <xs:annotation>
    <xs:documentation>
      XHTML Target Attribute Module
    </xs:documentation>
  </xs:annotation>
  Attributes defined here:
  target
  </xs:documentation>
  <xs:documentation source="http://www.w3.org/TR/xhtml-modularization/abstract_modules.html#s_targetmodule"/>
  </xs:annotation>
</xs:include>
</xs:schema>

```

A.4 XHTML+RDFa XML Schema Driver Module

You can download this version of this file from SCHEMA/xhtml-rdfa-2.xsd. The latest version is available at <http://www.w3.org/MarkUp/SCHEMA/xhtml-rdfa-2.xsd>.

```
<?xml version="1.0" encoding="UTF-8"?>
<xs:schema xmlns:xs="http://www.w3.org/2001/XMLSchema"
  targetNamespace="http://www.w3.org/1999/xhtml"
  xmlns:xh1ld="http://www.w3.org/1999/xhtml/datatypes/" xmlns="http://www.w3.org/1999/xhtml"
  elementFormDefault="qualified">
  <xs:annotation>
    <xs:documentation> This is the XML Schema driver for XHTML + RDFa Please use this namespace
      for XHTML elements: "http://www.w3.org/1999/xhtml" $Id: xhtml-rdfa-1.xsd,v 1.2
      2008/07/02 13:26:46 ahby Exp $ </xs:documentation>
    <xs:documentation source="xhtml-copyright-1.xsd"/>
  </xs:annotation>
  <xs:annotation>
    <xs:documentation> This is the Schema Driver file for XHTML + RDFa Document Type This schema
      + imports external schemas (xml.xsd) + refdefines (and include)s schema modules for
      XHTML1.1 Document Type. + includes Schema for Named content model for the XHTML1.1
      Document Type XHTML1.1 Document Type includes the following Modules XHTML Core modules
      (Required for XHTML Family Conformance) + text + hypertext + lists + structure Other
      XHTML modules + Edit + Bdo + Presentational + Link + Meta + Base + Scripting + Style +
      Image + Applet + Object + Param (Applet/Object modules require Param Module) + Tables +
      Forms + Client side image maps + Server side image maps + Ruby </xs:documentation>
  </xs:annotation>
  <xs:import namespace="http://www.w3.org/XML/1998/namespace"
    schemaLocation="http://www.w3.org/2001/xml.xsd">
    <xs:annotation>
      <xs:documentation> This import brings in the XML namespace attributes The XML attributes
        are used by various modules. </xs:documentation>
    </xs:annotation>
  </xs:import>
  <xs:import namespace="http://www.w3.org/1999/xhtml/datatypes/"
    schemaLocation="xhtml-datatypes-1.xsd"/>
  <xs:include schemaLocation="xhtml-rdfa-model-2.xsd">
    <xs:annotation>
      <xs:documentation> Document Model module for the XHTML+RDFa Document Type. This schema
        file defines all named models used by XHTML Modularization Framework for XHTML+RDFa
        Document Type </xs:documentation>
    </xs:annotation>
  </xs:include>
  <xs:include schemaLocation="xhtml-rdfa-modules-2.xsd">
    <xs:annotation>
      <xs:documentation> Schema that includes all modules (and redefinitions) for XHTML1.1
        Document Type. </xs:documentation>
    </xs:annotation>
  </xs:include>
  <!-- link, meta, and a need to be defined directly here -->
  <xs:attributeGroup name="xhtml.a.attlist">
    <xs:attributeGroup ref="xhtml.Common.attrib"/>
    <xs:attribute name="href" type="xh1ld:URI"/>
    <xs:attribute name="charset" type="xh1ld:Charset"/>
    <xs:attribute name="type" type="xh1ld:ContentType"/>
    <xs:attribute name="hreflang" type="xh1ld:LanguageCode"/>
    <xs:attribute name="accesskey" type="xh1ld:Character"/>
    <xs:attribute name="tabindex" type="xh1ld:Number"/>
    <xs:attributeGroup ref="xhtml.a.csim.attlist">
      <xs:annotation>
        <xs:documentation>
          Redefinition by Client Side Image Map Module
        </xs:documentation>
      </xs:annotation>
    </xs:attributeGroup>
    <xs:attributeGroup ref="xhtml.a.events.attlist">
      <xs:annotation>
```

```

        <xs:documentation>
            Redefinition by XHTML Event Attribute Module
        </xs:documentation>
    </xs:annotation>
</xs:attributeGroup>
<xs:attributeGroup ref="xhtml.a.target.attlist">
    <xs:annotation>
        <xs:documentation>
            Target Module - A Attribute Additions
        </xs:documentation>
    </xs:annotation>
</xs:attributeGroup>
</xs:attributeGroup>
<xs:group name="xhtml.a.content">
    <xs:sequence>
        <xs:group ref="xhtml.InlNoAnchor.mix" minOccurs="0" maxOccurs="unbounded"/>
    </xs:sequence>
</xs:group>
<xs:complexType name="xhtml.a.type" mixed="true">
    <xs:group ref="xhtml.a.content"/>
    <xs:attributeGroup ref="xhtml.a.attlist"/>
</xs:complexType>
<xs:attributeGroup name="xhtml.link.attlist">
    <xs:attributeGroup ref="xhtml.Common.attrib"/>
    <xs:attribute name="charset" type="xh11d:Charset"/>
    <xs:attribute name="href" type="xh11d:URI"/>
    <xs:attribute name="hreflang" type="xh11d:LanguageCode"/>
    <xs:attribute name="type" type="xh11d:ContentType"/>
    <xs:attribute name="media" type="xh11d:MediaDesc"/>
</xs:attributeGroup>
<xs:group name="xhtml.link.content">
    <xs:sequence/>
</xs:group>
<xs:complexType name="xhtml.link.type">
    <xs:group ref="xhtml.link.content"/>
    <xs:attributeGroup ref="xhtml.link.attlist"/>
</xs:complexType>
<xs:attributeGroup name="xhtml.meta.attlist">
    <xs:attributeGroup ref="xhtml.I18n.attrib"/>
    <xs:attribute ref="xml:space"/>
    <xs:attribute name="http-equiv" type="xs:NMTOKEN"/>
    <xs:attribute name="name" type="xs:NMTOKEN"/>
    <xs:attribute name="content" type="xh11d:CDATA" use="required"/>
    <xs:attribute name="scheme" type="xh11d:CDATA"/>
    <xs:attribute name="about" type="xh11d:URIorSafeCURIE"/>
    <xs:attribute name="datatype" type="xh11d:CURIE"/>
    <xs:attribute name="typeof" type="xh11d:CURIEs"/>
    <xs:attribute name="property" type="xh11d:CURIEs"/>
    <xs:attribute name="rel" type="xh11d:CURIEs"/>
    <xs:attribute name="resource" type="xh11d:URIorSafeCURIE"/>
    <xs:attribute name="rev" type="xh11d:CURIEs"/>
</xs:attributeGroup>
<xs:group name="xhtml.meta.content">
    <xs:sequence/>
</xs:group>
<xs:complexType name="xhtml.meta.type">
    <xs:group ref="xhtml.meta.content"/>
    <xs:attributeGroup ref="xhtml.meta.attlist"/>
</xs:complexType>

```


B. XHTML+RDFa Document Type Definition

This appendix includes an implementation of the XHTML+RDFa 1.1 language as an XML DTD. It is implemented by combining the XHTML 1.1 DTD with the XHTML Metainformation Attribute Module. This is done by using a content model module, and then a driver module. There are direct links to the various files, and the files are also contained in the "Gzip'd TAR" and "Zip" archives linked to at the top of this document. Please note that the files targeted by the "latest version" links may change slowly over time. See the W3C XHTML2 Working Group home page for more information.

B.1 XHTML Metainformation Attributes Module

You can download this version of this file from DTD/xhtml-metaAttributes-2.mod. The latest version is available at <http://www.w3.org/MarkUp/DTD/xhtml-metaAttributes-2.mod>.

```
<!-- ..... -->
<!-- XHTML MetaAttributes Module ..... -->
<!-- file: xhtml-metaAttributes-1.mod

This is XHTML-RDFa, modules to annotate XHTML family documents.
Copyright 2007-2008 W3C (MIT, ERCIM, Keio), All Rights Reserved.
Revision: $Id: Overview.html,v 1.12 2010/04/16 15:25:10 smccarro Exp $

This DTD module is identified by the PUBLIC and SYSTEM identifiers:

PUBLIC "-//W3C//ENTITIES XHTML MetaAttributes 1.0//EN"
SYSTEM "http://www.w3.org/MarkUp/DTD/xhtml-metaAttributes-1.mod"

Revisions:
(none)
..... -->

<!ENTITY % XHTML.global.attrs.prefixed "IGNORE" >

<!-- Placeholder Compact URI-related types -->
<!ENTITY % CURIE datatype "CDATA" >
<!ENTITY % CURIES datatype "CDATA" >
<!ENTITY % SafeCURIE datatype "CDATA" >
<!ENTITY % SafeCURIES datatype "CDATA" >
<!ENTITY % URIorCURIE datatype "CDATA" >
<!ENTITY % URIorCURIES datatype "CDATA" >
<!ENTITY % URIorSafeCURIE datatype "CDATA" >
<!ENTITY % URIorSafeCURIES datatype "CDATA" >

<!-- Common Attributes

This module declares a collection of meta-information related
attributes.

%NS.decl.attrib; is declared in the XHTML QName module.

This file also includes declarations of "global" versions of the
attributes. The global versions of the attributes are for use on
elements in other namespaces.
-->

<!ENTITY % about.attrib
  "about          %URIorCURIE.datatype;           #IMPLIED"
>

<![%XHTML.global.attrs.prefixed;
<!ENTITY % XHTML.global.about.attrib
  "%XHTML.prefix;:about            %URIorCURIE.datatype;           #IMPLIED"
>
]]>

<!ENTITY % typeof.attrib
  "typeof        %URIorCURIES.datatype;           #IMPLIED"
>

<![%XHTML.global.attrs.prefixed;
<!ENTITY % XHTML.global.typeof.attrib
  "%XHTML.prefix;:typeof            %URIorCURIES.datatype;           #IMPLIED"
>
]]>

<!ENTITY % property.attrib
  "property      %URIorCURIES.datatype;           #IMPLIED"
>

<![%XHTML.global.attrs.prefixed;
<!ENTITY % XHTML.global.property.attrib
  "%XHTML.prefix;:property          %URIorCURIES.datatype;           #IMPLIED"
>
]]>
```

```

<!ENTITY % resource.attrib
  "resource          %URIorCURIE.datatype;           #IMPLIED"
>

<![%XHTML.global.attrs.prefixed:[
<!ENTITY % XHTML.global.resource.attrib
  "%XHTML.prefix::resource          %URIorCURIE.datatype;           #IMPLIED"
>
]]>

<!ENTITY % content.attrib
  "content         CDATA           #IMPLIED"
>

<![%XHTML.global.attrs.prefixed:[
<!ENTITY % XHTML.global.content.attrib
  "%XHTML.prefix::content          CDATA           #IMPLIED"
>
]]>

<!ENTITY % datatype.attrib
  "datatype        %URIorCURIE.datatype;           #IMPLIED"
>

<![%XHTML.global.attrs.prefixed:[
<!ENTITY % XHTML.global.datatype.attrib
  "%XHTML.prefix::datatype          %URIorCURIE.datatype;           #IMPLIED"
>
]]>

<!ENTITY % rel.attrib
  "rel            %URIorCURIEs.datatype;           #IMPLIED"
>

<![%XHTML.global.attrs.prefixed:[
<!ENTITY % XHTML.global.rel.attrib
  "%XHTML.prefix::rel              %URIorCURIEs.datatype;           #IMPLIED"
>
]]>

<!ENTITY % rev.attrib
  "rev            %URIorCURIEs.datatype;           #IMPLIED"
>

<![%XHTML.global.attrs.prefixed:[
<!ENTITY % XHTML.global.rev.attrib
  "%XHTML.prefix::rev              %URIorCURIEs.datatype;           #IMPLIED"
>
]]>

<!ENTITY % prefix.attrib
  "prefix          %PREFIX.datatype;           #IMPLIED"
>

<![%XHTML.global.attrs.prefixed:[
<!ENTITY % XHTML.global.prefix.attrib
  "%XHTML.prefix::prefix            %PREFIX.datatype;           #IMPLIED"
>
]]>

<!ENTITY % vocab.attrib
  "vocab           %URI.datatype;           #IMPLIED"
>

<![%XHTML.global.attrs.prefixed:[
<!ENTITY % XHTML.global.vocab.attrib
  "%XHTML.prefix::vocab             %URI.datatype;           #IMPLIED"
>
]]>

<!ENTITY % Metainformation.extra.attrib "" >

<!ENTITY % Metainformation.attrib
  "%about.attrib;
  %content.attrib;
  %datatype.attrib;
  %typeof.attrib;
  %prefix.attrib;
  %property.attrib;
  %rel.attrib;
  %resource.attrib;
  %rev.attrib;
  %vocab.attrib;
  %Metainformation.extra.attrib;"*
>

<!ENTITY % XHTML.global.metainformation.extra.attrib "" >

<![%XHTML.global.attrs.prefixed:[
<!ENTITY % XHTML.global.metainformation.attrib
  "%XHTML.global.about.attrib;
  %XHTML.global.content.attrib;
  %XHTML.global.datatype.attrib;
  %XHTML.global.typeof.attrib;
  %XHTML.global.prefix.attrib;
  %XHTML.global.property.attrib;
  %XHTML.global.rel.attrib;
  %XHTML.global.resource.attrib;
  %XHTML.global.rev.attrib;
  %XHTML.global.vocab.attrib;
  %XHTML.global.metainformation.extra.attrib;"*
>
]]>

<!ENTITY % XHTML.global.metainformation.attrib "" >

```

```
<!-- end of XHTML+RDFa Document Model -->
```

B.2 XHTML+RDFa Content Model Module

You can download this version of this file from DTD/xhtml-rdfa-model-2.mod. The latest version is available at <http://www.w3.org/MarkUp/DTD/xhtml-rdfa-model-2.mod>.

```
<!-- ..... -->
<!-- XHTML+RDFa Document Model ..... -->
<!-- file: XHTML+RDFa Document Model -->

This is XHTML+RDFa.
Copyright 1998-2010 W3C (MIT, ERCIM, Keio), All Rights Reserved.
Revision: $Id: Overview.html,v 1.12 2010/04/16 15:25:10 smccarro Exp $ SMI

This DTD module is identified by the PUBLIC and SYSTEM identifiers:

PUBLIC "-//W3C//ENTITIES XHTML+RDFa Document Model 1.1//EN"
SYSTEM "http://www.w3.org/MarkUp/DTD/xhtml-rdfa-model-2.mod"

Revisions:
(none)
..... -->

<!-- XHTML+RDFa Document Model

This module describes the groupings of elements that make up
common content models for XHTML elements.

XHTML has three basic content models:

$Inline.mix; character-level elements
$block.mix; block-like elements, e.g., paragraphs and lists
$Flow.mix; any block or inline elements

Any parameter entities declared in this module may be used
to create element content models, but the above three are
considered 'global' (insofar as that term applies here).

The reserved word '#PCDATA' (indicating a text string) is now
included explicitly with each element declaration that is
declared as mixed content, as XML requires that this token
occur first in a content model specification.

-->
<!-- Extending the Model

While in some cases this module may need to be rewritten to
accommodate changes to the document model, minor extensions
may be accomplished by redeclaring any of the three *.extra;
parameter entities to contain extension element types as follows:

$Misc.extra; whose parent may be any block or
inline element.

$Inline.extra; whose parent may be any inline element.

$Block.extra; whose parent may be any block element.

If used, these parameter entities must be an OR-separated
list beginning with an OR separator ("|"), e.g., "| a | b | c"

All block and inline *.class parameter entities not part
of the *struct.class classes begin with "|" to allow for
exclusion from mixes.

-->
<!-- ..... Optional Elements in head .....
```

```
<!ENTITY % HeadOpts.mix
  "( %script.qname; | %style.qname; | %meta.qname;
  | %link.qname; | %object.qname; )*" >

<!-- ..... Miscellaneous Elements .....
```

```
<!-- ins and del are used to denote editing changes
-->
<!ENTITY % Edit.class "| %ins.qname; | %del.qname;" >

<!-- script and noscript are used to contain scripts
and alternative content
-->
<!ENTITY % Script.class "| %script.qname; | %noscript.qname;" >

<!ENTITY % Misc.extra "" >

<!-- These elements are neither block nor inline, and can
essentially be used anywhere in the document body.
-->
<!ENTITY % Misc.class
  "%Edit.class;
  %Script.class;
  %Misc.extra;" >

<!-- ..... Inline Elements .....
```

```

<!ENTITY % InlStruct.class "%br.qname; | %span.qname;" >
<!ENTITY % InlPhras.class
  "| %em.qname; | %strong.qname; | %dfn.qname; | %code.qname;
   | %samp.qname; | %kbd.qname; | %var.qname; | %cite.qname;
   | %abbr.qname; | %acronym.qname; | %q.qname;" >
<!ENTITY % InlPres.class
  "| %tt.qname; | %i.qname; | %b.qname; | %big.qname;
   | %small.qname; | %sub.qname; | %sup.qname;" >
<!ENTITY % I18n.class "| %bdo.qname;" >
<!ENTITY % Anchor.class "| %a.qname;" >
<!ENTITY % InlSpecial.class
  "| %img.qname; | %map.qname;
   | %object.qname;" >
<!ENTITY % InlForm.class
  "| %input.qname; | %select.qname; | %textarea.qname;
   | %label.qname; | %button.qname;" >
<!ENTITY % Inline.extra "" >
<!ENTITY % Ruby.class "| %ruby.qname;" >
<!-- %Inline.class; includes all inline elements,
     used as a component in mixes
-->
<!ENTITY % Inline.class
  "%InlStruct.class;
   %InlPhras.class;
   %InlPres.class;
   %I18n.class;
   %Anchor.class;
   %InlSpecial.class;
   %InlForm.class;
   %Ruby.class;
   %Inline.extra;" >
<!-- %InlNoRuby.class; includes all inline elements
     except ruby, used as a component in mixes
-->
<!ENTITY % InlNoRuby.class
  "%InlStruct.class;
   %InlPhras.class;
   %InlPres.class;
   %I18n.class;
   %Anchor.class;
   %InlSpecial.class;
   %InlForm.class;
   %Inline.extra;" >
<!-- %NRuby.content; includes all inlines except ruby
-->
<!ENTITY % NoRuby.content
  "( #PCDATA
   | %InlNoRuby.class;
   %Misc.class; )**" >
<!-- %InlNoAnchor.class; includes all non-anchor inlines,
     used as a component in mixes
-->
<!ENTITY % InlNoAnchor.class
  "%InlStruct.class;
   %InlPhras.class;
   %InlPres.class;
   %I18n.class;
   %InlSpecial.class;
   %InlForm.class;
   %Ruby.class;
   %Inline.extra;" >
<!-- %InlNoAnchor.mix; includes all non-anchor inlines
-->
<!ENTITY % InlNoAnchor.mix
  "%InlNoAnchor.class;
   %Misc.class;" >
<!-- %Inline.mix; includes all inline elements, including %Misc.class;
-->
<!ENTITY % Inline.mix
  "%Inline.class;
   %Misc.class;" >
<!-- ..... Block Elements ..... -->
<!-- In the HTML 4.0 DTD, heading and list elements were included
     in the %block; parameter entity. The %Heading.class; and
     %List.class; parameter entities must now be included explicitly
     on element declarations where desired.
-->
<!ENTITY % Heading.class
  "%h1.qname; | %h2.qname; | %h3.qname;
   | %h4.qname; | %h5.qname; | %h6.qname;" >
<!ENTITY % List.class "%ul.qname; | %ol.qname; | %dl.qname;" >

```

```

<!ENTITY % Table.class "| %table.qname;" >
<!ENTITY % Form.class "| %form.qname;" >
<!ENTITY % Fieldset.class "| %fieldset.qname;" >
<!ENTITY % BlkStruct.class "%p.qname; | %div.qname;" >
<!ENTITY % BlkPhras.class
  "| %pre.qname; | %blockquote.qname; | %address.qname;" >
<!ENTITY % BlkPres.class "| %hr.qname;" >
<!ENTITY % BlkSpecial.class
  "%Table.class;
  %Form.class;
  %Fieldset.class;" >
<!ENTITY % Block.extra "" >
<!-- %Block.class; includes all block elements,
     used as an component in mixes
-->
<!ENTITY % Block.class
  "%BlkStruct.class;
  %BlkPhras.class;
  %BlkPres.class;
  %BlkSpecial.class;
  %Block.extra;" >
<!-- ..... All Content Elements ..... -->
<!-- %Flow.mix; includes all text content, block and inline
-->
<!ENTITY % Flow.mix
  "%Heading.class;
  | %List.class;
  | %Block.class;
  | %Inline.class;
  %Misc.class;" >
>
<!-- end of xhtml-rdfa-model-2.mod -->

```

B.3 XHTML+RDFa Driver Module

You can download this version of this file from DTD/xhtml-rdfa-2.dtd. The latest version is available at <http://www.w3.org/MarkUp/DTD/xhtml-rdfa-2.dtd>.

```

<!-- ..... -->
<!-- XHTML 1.1 + RDFa DTD ..... -->
<!-- file: xhtml-rdfa-2.dtd
-->

<!-- XHTML 1.1 + RDFa DTD

This is an example markup language combining XHTML 1.1 and the RDFa
modules.

XHTML+RDFa
Copyright 1998-2010 World Wide Web Consortium
(Massachusetts Institute of Technology, European Research Consortium
for Informatics and Mathematics, Keio University).
All Rights Reserved.

Permission to use, copy, modify and distribute the XHTML DTD and its
accompanying documentation for any purpose and without fee is hereby
granted in perpetuity, provided that the above copyright notice and
this paragraph appear in all copies. The copyright holders make no

```

representation about the suitability of the DTD for any purpose.

It is provided "as is" without expressed or implied warranty.

-->

<!-- This is the driver file for version 1 of the XHTML + RDFa DTD.

Please use this public identifier to identify it:

"-//W3C//DTD XHTML+RDFa 1.1//EN"

-->

<!ENTITY % XHTML.version "XHTML+RDFa 1.1" >

<!-- Use this URI to identify the default namespace:

"http://www.w3.org/1999/xhtml"

See the Qualified Names module for information
on the use of namespace prefixes in the DTD.

Note that XHTML namespace elements are not prefixed by default,
but the XHTML namespace prefix is defined as "xhtml" so that
other markup languages can extend this one and use the XHTML
prefixed global attributes if required.

-->

<!ENTITY % NS.prefixes "IGNORE" >
<!ENTITY % XHTML.prefix "xhtml" >

<!-- Be sure to include prefixed global attributes - we don't need
them, but languages that extend XHTML 1.1 might.

-->

<!ENTITY % XHTML.global.attrs.prefixes "INCLUDE" >

<!-- Reserved for use with the XLink namespace:

-->

<!ENTITY % XLINK.xmlns "" >
<!ENTITY % XLINK.xmlns.attrib "" >

<!-- For example, if you are using XHTML 1.1 directly, use the public
identifier in the DOCTYPE declaration, with the namespace declaration
on the document element to identify the default namespace:

```
<?xml version="1.0"?>
<!DOCTYPE html PUBLIC "-//W3C//DTD XHTML+RDFa 1.1//EN"
           "http://www.w3.org/MarkUp/DTD/xhtml-rdfa-2.dtd">
<html xmlns="http://www.w3.org/1999/xhtml"
      xml:lang="en">
  ...
</html>
```

Revisions:

(none)

-->

<!-- reserved for future use with document profiles -->
<!ENTITY % XHTML.profile "" >

```

<!-- ensure XHTML Notations are disabled -->
<!ENTITY % xhtml-notations.module "IGNORE" >

<!-- Bidirectional Text features
      This feature-test entity is used to declare elements
      and attributes used for bidirectional text support.
-->
<!ENTITY % XHTML.bidi    "INCLUDE" >

<!-- ::::::::::::::::::::::::::::::::::::::::::::::: -->

<!-- Pre-Framework Redeclaration placeholder ..... -->
<!-- this serves as a location to insert markup declarations
      into the DTD prior to the framework declarations.
-->
<!ENTITY % xhtml-prefw-redecl.module "IGNORE" >
<!ENTITY % xhtml-prefw-redecl.mod "" >
<![%xhtml-prefw-redecl.module;[
  %xhtml-prefw-redecl.mod;
<!-- end of xhtml-prefw-redecl.module -->]]>

<!-- we need the datatypes now -->
<!ENTITY % xhtml-datatYPES.module "INCLUDE" >
<![%xhtml-datatYPES.module;[
<!ENTITY % xhtml-datatYPES.mod
  PUBLIC "-//W3C//ENTITIES XHTML Datatypes 1.0//EN"
  "http://www.w3.org/MarkUp/DTD/xhtml-datatYPES-1.mod" >
  %xhtml-datatYPES.mod;]]>

<!-- bring in the RDFa attributes cause we need them in Common -->
<!ENTITY % xhtml-metaAttributes.module "INCLUDE" >
<![%xhtml-metaAttributes.module;[
<!ENTITY % xhtml-metaAttributes.mod
  PUBLIC "-//W3C//ENTITIES XHTML MetaAttributes 1.1//EN"
  "http://www.w3.org/MarkUp/DTD/xhtml-metaAttributes-2.mod" >
  %xhtml-metaAttributes.mod;]]>

<!ENTITY % xhtml-events.module "INCLUDE" >

<!ENTITY % Common.extra.attrib
  "href          %URI.datatype;           #IMPLIED
   %Metainformation.attrib;" >
<!-- adding the lang attribute into the I18N collection -->

<!ENTITY % lang.attrib
  "xml:lang     %LanguageCode.datatype; #IMPLIED
   lang        %LanguageCode.datatype; #IMPLIED" >

<!-- Inline Style Module ..... -->
<!ENTITY % xhtml-inlstyle.module "INCLUDE" >
<![%xhtml-inlstyle.module;[
<!ENTITY % xhtml-inlstyle.mod
  PUBLIC "-//W3C//ELEMENTS XHTML Inline Style 1.0//EN"
  "http://www.w3.org/MarkUp/DTD/xhtml-inlstyle-1.mod" >

```

```
%xhtml-inlstyle.mod;]]>

<!-- declare Document Model module instantiated in framework
-->
<!ENTITY % xhtml-model.mod
  PUBLIC "-//W3C//ENTITIES XHTML+RDFa Document Model 1.1//EN"
  "http://www.w3.org/MarkUp/DTD/xhtml-rdfa-model-2.mod" >

<!-- Modular Framework Module (required) ..... -->
<!ENTITY % xhtml-framework.module "INCLUDE" >
<![%xhtml-framework.module;[
<!ENTITY % xhtml-framework.mod
  PUBLIC "-//W3C//ENTITIES XHTML Modular Framework 1.0//EN"
  "http://www.w3.org/MarkUp/DTD/xhtml-framework-1.mod" >
%xhtml-framework.mod;]]>

<!-- Post-Framework Redeclaration placeholder ..... -->
<!-- this serves as a location to insert markup declarations
     into the DTD following the framework declarations.
-->
<!ENTITY % xhtml-postfw-redecl.module "IGNORE" >
<!ENTITY % xhtml-postfw-redecl.mod "">
<![%xhtml-postfw-redecl.module;[
%xhtml-postfw-redecl.mod;
<!-- end of xhtml-postfw-redecl.module -->]]>

<!-- Text Module (Required) ..... -->
<!ENTITY % xhtml-text.module "INCLUDE" >
<![%xhtml-text.module;[
<!ENTITY % xhtml-text.mod
  PUBLIC "-//W3C//ELEMENTS XHTML Text 1.0//EN"
  "http://www.w3.org/MarkUp/DTD/xhtml-text-1.mod" >
%xhtml-text.mod;]]>

<!-- Hypertext Module (required) ..... -->
<!ENTITY % a.attlist "IGNORE" >
<!ENTITY % xhtml-hypertext.module "INCLUDE" >
<![%xhtml-hypertext.module;[
<!ENTITY % xhtml-hypertext.mod
  PUBLIC "-//W3C//ELEMENTS XHTML Hypertext 1.0//EN"
  "http://www.w3.org/MarkUp/DTD/xhtml-hypertext-1.mod" >
%xhtml-hypertext.mod;]]>
<!ATTLIST %a.qname;
  %Common.attrib;
  charset      %Charset.datatype;      #IMPLIED
  type         %ContentType.datatype;   #IMPLIED
  hreflang     %LanguageCode.datatype;  #IMPLIED
  accesskey    %Character.datatype;    #IMPLIED
  tabindex     %Number.datatype;       #IMPLIED
>

<!-- Lists Module (required) ..... -->
<!ENTITY % xhtml-list.module "INCLUDE" >
<![%xhtml-list.module;[
<!ENTITY % xhtml-list.mod
```

```

PUBLIC "-//W3C//ELEMENTS XHTML Lists 1.0//EN"
      "http://www.w3.org/MarkUp/DTD/xhtml-list-1.mod" >
%xhtml-list.mod;]]>

<!-- :::::::::::::::::::::::::::::::::::::::::::::::::::::: -->

<!-- Edit Module ..... -->
<!ENTITY % xhtml-edit.module "INCLUDE" >
<![%xhtml-edit.module;[
<!ENTITY % xhtml-edit.mod
    PUBLIC "-//W3C//ELEMENTS XHTML Editing Elements 1.0//EN"
        "http://www.w3.org/MarkUp/DTD/xhtml-edit-1.mod" >
%xhtml-edit.mod;]]>

<!-- BIDI Override Module ..... -->
<!ENTITY % xhtml-bdo.module "%XHTML.bidi;" >
<![%xhtml-bdo.module;[
<!ENTITY % xhtml-bdo.mod
    PUBLIC "-//W3C//ELEMENTS XHTML BIDI Override Element 1.0//EN"
        "http://www.w3.org/MarkUp/DTD/xhtml-bdo-1.mod" >
%xhtml-bdo.mod;]]>

<!-- Ruby Module ..... -->
<!ENTITY % Ruby.common.attlists "INCLUDE" >
<!ENTITY % Ruby.common.attrib "%Common.attrib;" >
<!ENTITY % xhtml-ruby.module "INCLUDE" >
<![%xhtml-ruby.module;[
<!ENTITY % xhtml-ruby.mod
    PUBLIC "-//W3CWorld Wide Web//ELEMENTS XHTML Ruby 1.0//EN"
        "http://www.w3.org/TR/ruby/xhtml-ruby-1.mod" >
%xhtml-ruby.mod;]]>

<!-- Presentation Module ..... -->
<!ENTITY % xhtml-pres.module "INCLUDE" >
<![%xhtml-pres.module;[
<!ENTITY % xhtml-pres.mod
    PUBLIC "-//W3C//ELEMENTS XHTML Presentation 1.0//EN"
        "http://www.w3.org/MarkUp/DTD/xhtml-pres-1.mod" >
%xhtml-pres.mod;]]>

<!ENTITY % link.attlist "IGNORE" >
<!-- Link Element Module ..... -->
<!ENTITY % xhtml-link.module "INCLUDE" >
<![%xhtml-link.module;[
<!ENTITY % xhtml-link.mod
    PUBLIC "-//W3C//ELEMENTS XHTML Link Element 1.0//EN"
        "http://www.w3.org/MarkUp/DTD/xhtml-link-1.mod" >
%xhtml-link.mod;]]>

<!ATTLIST %link.qname;
  %Common.attrib;
  charset      %Charset.datatype;      #IMPLIED
  hreflang     %LanguageCode.datatype;  #IMPLIED
  type         %ContentType.datatype;   #IMPLIED
  media        %MediaDesc.datatype;     #IMPLIED
>
```

```

<!-- Document Metainformation Module ..... -->
<!ENTITY % meta.attlist "IGNORE" >
<!ENTITY % xhtml-meta.module "INCLUDE" >
<![%xhtml-meta.module;[
<!ENTITY % xhtml-meta.mod
    PUBLIC "-//W3C//ELEMENTS XHTML Metainformation 1.0//EN"
    "http://www.w3.org/MarkUp/DTD/xhtml-meta-1.mod" >
%xhtml-meta.mod;]]>
<!ATTLIST %meta.qname;
    %Common.attrib;
    http-equiv NMTOKEN          #IMPLIED
    name        NMTOKEN          #IMPLIED
    scheme      CDATA            #IMPLIED
>

<!-- Base Element Module ..... -->
<!ENTITY % xhtml-base.module "INCLUDE" >
<![%xhtml-base.module;[
<!ENTITY % xhtml-base.mod
    PUBLIC "-//W3C//ELEMENTS XHTML Base Element 1.0//EN"
    "http://www.w3.org/MarkUp/DTD/xhtml-base-1.mod" >
%xhtml-base.mod;]]>

<!-- Scripting Module ..... -->
<!ENTITY % script.attlist "IGNORE" >
<!ENTITY % xhtml-script.module "INCLUDE" >
<![%xhtml-script.module;[
<!ENTITY % xhtml-script.mod
    PUBLIC "-//W3C//ELEMENTS XHTML Scripting 1.0//EN"
    "http://www.w3.org/MarkUp/DTD/xhtml-script-1.mod" >
%xhtml-script.mod;]]>

<!ATTLIST %script.qname;
    %XHTML.xmlns.attrib;
    %id.attrib;
    %Metainformation.attrib;
    href      %URI.datatype;      #IMPLIED
    xml:space ( preserve )        #FIXED 'preserve'
    charset   %Charset.datatype;  #IMPLIED
    type      %ContentType.datatype; #required
    src       %URI.datatype;      #IMPLIED
    defer     ( defer )          #IMPLIED
>

<!-- Style Sheets Module ..... -->
<!ENTITY % style.attlist "IGNORE" >
<!ENTITY % xhtml-style.module "INCLUDE" >
<![%xhtml-style.module;[
<!ENTITY % xhtml-style.mod
    PUBLIC "-//W3C//ELEMENTS XHTML Style Sheets 1.0//EN"
    "http://www.w3.org/MarkUp/DTD/xhtml-style-1.mod" >
%xhtml-style.mod;]]>
<!ATTLIST %style.qname;
    %XHTML.xmlns.attrib;
    %id.attrib;
    %title.attrib;
    %I18n.attrib;

```

```

%Metainformation.attrib;
href          %URI.datatype;           #IMPLIED
xml:space    ( preserve )            #FIXED 'preserve'
type         %ContentType.datatype;  #required
media        %MediaDesc.datatype;    #IMPLIED
>

<!-- Image Module ..... -->
<!ENTITY % xhtml-image.module "INCLUDE" >
<![%xhtml-image.module;[
<!ENTITY % xhtml-image.mod
  PUBLIC "-//W3C//ELEMENTS XHTML Images 1.0//EN"
  "http://www.w3.org/MarkUp/DTD/xhtml-image-1.mod" >
%xhtml-image.mod;]]>

<!-- Client-side Image Map Module ..... -->
<!ENTITY % area.attlist "IGNORE" >

<!ENTITY % xhtml-csismap.module "INCLUDE" >
<![%xhtml-csismap.module;[
<!ENTITY % xhtml-csismap.mod
  PUBLIC "-//W3C//ELEMENTS XHTML Client-side Image Maps 1.0//EN"
  "http://www.w3.org/MarkUp/DTD/xhtml-csismap-1.mod" >
%xhtml-csismap.mod;]]>

<!ATTLIST %area.qname;
  %Common.attrib;
  shape      %Shape.datatype;        'rect'
  coords     %Coords.datatype;      #IMPLIED
  nohref    ( nohref )             #IMPLIED
  alt        %Text.datatype;        #required
  tabindex   %Number.datatype;      #IMPLIED
  accesskey  %Character.datatype;  #IMPLIED
>

<!-- Server-side Image Map Module ..... -->
<!ENTITY % xhtml-ssismap.module "INCLUDE" >
<![%xhtml-ssismap.module;[
<!ENTITY % xhtml-ssismap.mod
  PUBLIC "-//W3C//ELEMENTS XHTML Server-side Image Maps 1.0//EN"
  "http://www.w3.org/MarkUp/DTD/xhtml-ssismap-1.mod" >
%xhtml-ssismap.mod;]]>

<!-- Param Element Module ..... -->
<!ENTITY % param.attlist "IGNORE" >
<!ENTITY % xhtml-param.module "INCLUDE" >
<![%xhtml-param.module;[
<!ENTITY % xhtml-param.mod
  PUBLIC "-//W3C//ELEMENTS XHTML Param Element 1.0//EN"
  "http://www.w3.org/MarkUp/DTD/xhtml-param-1.mod" >
%xhtml-param.mod;]]>

<!ATTLIST %param.qname;
  %XHTML.xmlns.attrib;
  %id.attrib;
  %Metainformation.attrib;
  href      %URI.datatype;          #IMPLIED

```

```

name          CDATA           #required
value         CDATA           #IMPLIED
valuetype    ( data | ref | object ) 'data'
type          %ContentType.datatype; #IMPLIED
>
<!-- Embedded Object Module ..... -->
<!ENTITY % xhtml-object.module "INCLUDE" >
<![%xhtml-object.module;[
<!ENTITY % xhtml-object.mod
  PUBLIC "-//W3C//ELEMENTS XHTML Embedded Object 1.0//EN"
  "http://www.w3.org/MarkUp/DTD/xhtml-object-1.mod" >
%xhtml-object.mod;]]>

<!-- Tables Module ..... -->
<!ENTITY % xhtml-table.module "INCLUDE" >
<![%xhtml-table.module;[
<!ENTITY % xhtml-table.mod
  PUBLIC "-//W3C//ELEMENTS XHTML Tables 1.0//EN"
  "http://www.w3.org/MarkUp/DTD/xhtml-table-1.mod" >
%xhtml-table.mod;]]>

<!-- Forms Module ..... -->
<!ENTITY % xhtml-form.module "INCLUDE" >
<![%xhtml-form.module;[
<!ENTITY % xhtml-form.mod
  PUBLIC "-//W3C//ELEMENTS XHTML Forms 1.0//EN"
  "http://www.w3.org/MarkUp/DTD/xhtml-form-1.mod" >
%xhtml-form.mod;]]>

<!-- Target Attribute Module ..... -->
<!ENTITY % xhtml-target.module "INCLUDE" >
<![%xhtml-target.module;[
<!ENTITY % xhtml-target.mod
  PUBLIC "-//W3C//ELEMENTS XHTML Target 1.0//EN"
  "http://www.w3.org/MarkUp/DTD/xhtml-target-1.mod" >
%xhtml-target.mod;]]>

<!-- Legacy Markup ..... -->
<!ENTITY % xhtml-legacy.module "IGNORE" >
<![%xhtml-legacy.module;[
<!ENTITY % xhtml-legacy.mod
  PUBLIC "-//W3C//ELEMENTS XHTML Legacy Markup 1.0//EN"
  "http://www.w3.org/MarkUp/DTD/xhtml-legacy-1.mod" >
%xhtml-legacy.mod;]]>

<!-- Document Structure Module (required) ..... -->
<!ENTITY % html.attlist  "IGNORE" >
<!ENTITY % head.attlist  "IGNORE" >
<!ENTITY % title.attlist "IGNORE" >
<!ENTITY % xhtml-struct.module "INCLUDE" >
<![%xhtml-struct.module;[
<!ENTITY % xhtml-struct.mod
  PUBLIC "-//W3C//ELEMENTS XHTML Document Structure 1.0//EN"
  "http://www.w3.org/MarkUp/DTD/xhtml-struct-1.mod" >
%xhtml-struct.mod;]]>
<!ENTITY % profile.attrib
  "profile      %URI.datatype;           '%XHTML.profile;' "

```

```

>
<!ENTITY % XHTML.version.attrib
  "version      %FPI.datatype;          #FIXED '%XHTML.version;'"
>
<!ATTLIST %html.qname;
  %Common.attrib;
  %XSI.schemaLocation.attrib;
  %XHTML.version.attrib;
>
<!ATTLIST %head.qname;
  %Common.attrib;
  %profile.attrib;
>
<!ATTLIST %title.qname;
  %Common.attrib;
>

<!-- end of XHTML-RDFa DTD ..... --&gt;
&lt!-- ..... --&gt;
</pre>

```

B.4 SGML Open Catalog Entry for XHTML+RDFa

This section contains the SGML Open Catalog-format definition [SGML-CATALOG [p.60]] of the public identifiers for XHTML+RDFa 1.1.

You can download this version of this file from DTD/xhtml-rdfa.cat. The latest version is available at <http://www.w3.org/MarkUp/DTD/xhtml-rdfa.cat>.

```

-- ..... --
-- File catalog ..... --
-- XHTML+RDFa Catalog Data File

Revision: $Revision: 1.12 $

See "Entity Management", SGML Open Technical Resolution 9401 for detailed
information on supplying and using catalog data. This document is available
from OASIS at URL:

<http://www.oasis-open.org/html/tr9401.html>
--

-- ..... --
-- SGML declaration associated with XHTML ..... --
OVERRIDE YES

SGMLDECL "xml1.dcl"

-- ::::::::::::::::::::: --
-- XHTML+RDFa modules ..... --

PUBLIC "-//W3CWorld Wide Web//DTD XHTML+RDFa 1.0//EN"      "xhtml-rdfa-1.dtd"
PUBLIC "-//W3C//ENTITIES XHTML+RDFa Document Model 1.0//EN"    "xhtml-rdfa-model-1.mod"

```

```
PUBLIC "-//W3C//ENTITIES XHTML MetaAttributes 1.0//EN"           "xhtml-metaAttributes-1.mod"
-- End of catalog data ..... --  
-- .....
```

C. Deployment Advice

This section is non-normative.

Documents written using the markup language defined in this specification can be validated using the DTD defined in Appendix A [p.39] . If a document author wants to facilitate such validation, they may include the following declaration at the top of their document:

```
<!DOCTYPE html PUBLIC "-//W3C//DTD XHTML+RDFa 1.1//EN"
 "http://www.w3.org/MarkUp/DTD/xhtml-rdfa-2.dtd">
```

The XML Namespace document associated with the XHTML Family of markup languages uses the mechanism for transforming XHTML+RDFa documents into RDF as defined by [GRDDL [p.59]]. Authors who want to be certain their documents are transformable by all [GRDDL [p.59]] processors may also include a `profile` attribute on the `head` element that includes a reference to the XHTML vocabulary URI <http://www.w3.org/1999/xhtml/vocab>.

D. Change History

This section is non-normative.

2010-02-25: First version of the split-out XHTML specialization.

E. Acknowledgments

This section is non-normative.

At the time of publication, the members of the RDFa Working Group were:

- Ben Adida, Creative Commons (Co-Chair)
- Benjamin Adrian, German Research Center for Artificial Intelligence (DFKI) GmbH
- Mark Birbeck, webBackplane.com (Invited Expert)
- Abhijit Galkward, Rochester Institute of Technology
- Markus Gylling, DAISY Consortium
- Ivan Herman, W3C
- Toby Inkster (Invited Expert)
- Shane McCarron, Applied Testing and Technology, Inc. (Invited Expert)
- Knud MÃ¶ller (DERI Galway at the National University of Ireland)
- John O'Donovan, British Broadcasting Corporation
- Steven Pemberton, Centre for Mathematics and Computer Science (CWI)
- Jeffrey Sonstein, Rochester Institute of Technology
- Manu Sporny, Digital Bazaar (Co-Chair, Invited Expert)
- Robert Weir, IBM Corporation

F. References

F.1 Normative references

[HTML401]

David Raggett; Ian Jacobs; Arnaud Le Hors. *HTML 4.01 Specification*. 24 December 1999. W3C Recommendation. URL: <http://www.w3.org/TR/1999/REC-html401-19991224>

[RDFA-CORE]

Shane McCarron, et al. *RDFa Core 1.1: Syntax and processing rules for embedding RDF through attributes*. 1 April 2010. W3C Editor's Draft. URL: <http://www.w3.org/2010/02/rdfa/drafts>

[RFC2119]

S. Bradner. *Key words for use in RFCs to Indicate Requirement Levels*. Internet RFC 2119. URL: <http://www.ietf.org/rfc/rfc2119.txt>

[RFC3236]

P. Stark; M. Baker. *The 'application/xhtml+xml' Media Type*. January 2002. Internet RFC 3236. URL: <http://www.rfc-editor.org/rfc/rfc3236.txt>

[RUBY]

Masayasu Ishikawa; et al. *Ruby Annotation*. 31 May 2001. W3C Recommendation. URL: <http://www.w3.org/TR/2001/REC-ruby-20010531>

[XHTML-MODULARIZATION11-2e]

Shane McCarron. *XHTMLâ¢ Modularization 1.1 Second Edition*. 14 April 2010. W3C Proposed Edited Recommendation. URL: <http://www.w3.org/TR/2010/PER-xhtml-modularization-20100414>

[XHTML11-2e]

Masayasu Ishikawa; Shane McCarron. *XHTMLâ¢ 1.1 - Module-based XHTML - Second Edition*. 16 February 2007. W3C Working Draft. (Work in progress.) URL: <http://www.w3.org/TR/2007/WD-xhtml11-20070216>

[XML-NAMES11]

Andrew Layman; et al. *Namespaces in XML 1.1 (Second Edition)*. 16 August 2006. W3C Recommendation. URL: <http://www.w3.org/TR/2006/REC-xml-names11-20060816>

[XMLSCHEMA-2]

Paul V. Biron; Ashok Malhotra. *XML Schema Part 2: Datatypes Second Edition*. 28 October 2004. W3C Recommendation. URL: <http://www.w3.org/TR/2004/REC-xmlschema-2-20041028/>

F.2 Informative references

[GRDDL]

Dan Connolly. *Gleaning Resource Descriptions from Dialects of Languages (GRDDL)*. 11 September 2007. W3C Recommendation. URL: <http://www.w3.org/TR/2007/REC-grddl-20070911>

[RDFA-SYNTAX]

Ben Adida, et al. *RDFa in XHTML: Syntax and Processing*. 14 October 2008. W3C Recommendation. URL: <http://www.w3.org/TR/2008/REC-rdfa-syntax-20081014>

[SGML-CATALOG]

Paul Grosso. *Entity Management: OASIS Technical Resolution 9401:1997 (Amendment 2 to TR 9401)* 10 september 1007. Entity Management Subcommittee, SGML Open. URL: <http://www.oasis-open.org/html/a401.htm>

[XHTML-MEDIA-TYPES]

Shane McCarron. *XHTML Media Types - Second Edition*. 16 January 2009. W3C Note. URL: <http://www.w3.org/TR/2009/NOTE-xhtml-media-types-20090116>

[XHTML-VOCAB]

XHTML 2 Working Group. *XHTML Vocabulary*. URL: <http://www.w3.org/1999/xhtml/vocab>